

Safety Data Sheet

1. Identification of the substance or mixture and of the supplier

Product name : Vitrified Bond Wheels : WA Grinding Wheel
 Reference number : MSDS-WA Grinding Wheel
 Company name : Kure Grinding Wheel, Co., Ltd
 Address : 3-20 2-chome, Yoshiura-shinmachi, Kure-shi, Hiroshima Pref. 737-8518, Japan
 Recommended use and restrictions of operation : For grinding metal and non-metal

2. Hazard identification

Vitrified bond wheels are mixtures of abrasive grains and vitrified material. The hazard statements are stated as below:

The hazardous statements of substances which are components of grinding wheels, are listed by

Global Harmonized System classification as below, which apply Industrial Safety and Health Act Article 57-2

and Law concerning Pollutant Release and Transfer Register in Japan.

- Hazards : If grinding wheel burst during operation and pieces of an accidentally broken wheel hit a person, it may cause injury or death.
Sparks generated by grinding can cause burn wound and fire.
- Environmental effects : Dust generated by grinding can contaminate the working environment.

GHS classification of the mixtures

	Aluminum Oxide	Amorphous Silica	Diboron Trioxide
Physical hazards	Not applicable	Not applicable	Not applicable
Health hazards			
Acute toxicity (Oral)	Not classified	Not applicable	Category 5
Skin corrosion/irritation	Not applicable	Not applicable	Category 3
Serious eye damage/eye irritation	Not applicable	Not applicable	Category 2A or 2B
Specific target organ and systemic toxicity following single exposure	Category 3 (Respiratory tract irritation)	Not applicable	Category 3 (Respiratory tract irritation)
Specific target organ and systemic toxicity -Repeated exposure	Category 1 (Inhalation: Lungs)	Not applicable	Not applicable
Environmental hazards	Not applicable	Not applicable	Not applicable

Label elements

Name of the substance	Aluminum Oxide	Amorphous Silica	Diboron Trioxide
Pictogram		No data	
Signal word	Danger	No data	Warning
Hazards statements	Causes damage to organs through prolonged or repeated exposure (Inhalation: Lungs) (Respiratory tract irritation) May cause respiratory irritation	No data	May be harmful if swallowed Causes serious eye irritation Causes mild skin irritation (Respiratory tract irritation) May cause respiratory irritation

3. Composition/information on ingredients

< Identification of the substance > Classification of hazardous substances and mixtures : Mixture of silicon carbide and vitrified material.

Information on ingredients

Name	Molecular formula or structural formula	Industrial Safety and Health Act Cabinet Order Number or Chemical Substances Control Law Class Reference Number in the Gazette List of Japan	C A S number	Regulatory information
Aluminum Oxide	Al ₂ O ₃	189 (1)-23	1344-28-1	Industrial Safety and Health Act
Amorphous Silica, Silicon Dioxide	SiO ₂	312 (1)-548	60676-86-0	Industrial Safety and Health Act
Diboron Trioxide	B ₂ O ₃	196 (1)-71	1303-86-2	Industrial Safety and Health Act (of Japan)

Note: The weight percent will be less than 1% if converted to boron (B), which is not applicable for PRTR Law's reporting requirement.

4. First-aid measures

- If inhaled : If inhaled dust, immediately remove person to fresh air, rinse mouth with plenty of water, and keep comfortable for breathing.
- If on skin : Do not rub, and wash affected area with soap and water after handling.
- If swallowed : Do not induce vomiting.
- If a part of the grinding wheel or workpiece hit directly a human
: (If a high-speed rotating grinding wheel burst during operation and a part of the grinding wheel or workpiece hit directly the human body.)
- Expected immediate and delayed symptoms : If inhaled dust or mist of grinding fluid during operation, it may cause respiratory irritation; through prolonged exposure it may cause pneumoconiosis, delayed symptoms or damage to lungs.
- Most important signs and symptoms : If sparks from workpieces or chips blasted into the eye, it may cause ocular tissue damage such as burn injury.
- Protection for first-aiders : Stop the machine before providing first-aid.
- Precautions for doctors : Grinding wheels have abrasive grains with cutting edges on the surface, which may cause incised wound if contacted with human body.

5. Fire-fighting measures

- Extinguishing media : This product does not combust itself.
- Unsuitable extinguishing media : No information
- Unsuitable extinguishing media : Not applicable
- Specific ways to extinguish : Not applicable
- Protective equipment for fire-fighters : Not applicable. Use of suitable protective equipment is preferable.

6. Accidental Release Measures

- Personal precautions : If dust, etc. got in eyes, rinse cautiously with water for several minutes.
- Protective equipment and emergency procedures : When recovering dust, wear protective equipment (such as eye and respiratory protections). Wash hands after handling.
- Environmental precautions : Do not emit grinding chips to surface water. Dissolution of controlled substances in soil and water may occur.
- Recovery / neutralization : Not applicable
- Second disaster : Not applicable

7. Handling and storage

- Handling
- Technical measures : Before operation, read safety material of the product and related equipments, and do not handle until all safety precautions have been read and understood.
- Do not involve replacement of grinding wheels or their test runs without receiving Special Education.
 - Check if the Maximum Operation Speed and the diameter marked on the grinding wheel are adequate for the machine.
 - Prior to mounting, all grinding wheels shall be performed visual inspection and ring test for crack, and chipping.
 - Select proper flanges when mounting grinding wheels, and don't tighten the nut excessively.
 - Make a test run for one minute or longer before commencing the work for the day and for three minutes or longer when replacing a grinding wheel.
 - When mounting grinding wheels to flanges, always perform visual inspection and ring test to check there is no defect.
 - Always use flanges of materials and diameter according to legal requirement.
 - Do not use the side surfaces of a grinding wheel except for a grinding wheel designed for use of their side surfaces.
 - Furnish with required safety devices (ex. protection covers).
- Local exhaust ventilation and general ventilation : Provide local exhaust ventilation or general ventilation during grinding operation where dust is generated.
- Precautions for safe handling : 1. Do not drop wheels.
2. Do not bump wheels.
3. Do not roll wheels.
4. Avoid human contact with abrasive wheels during operation.
- Technical measures : Abrasive wheels should be stored in a dry area in rooms not subject to extreme temperature changes since some bonds may be affected by excessive humidity, dampness and extreme temperature differentials.
They should be stored on surface plates or in racks.
- Incompatible materials : Not applicable
- Conditions for storage : Grinding wheels shall be stored in rooms at normal temperatures and humidity. Grinding wheels shall not be stored subject to freezing temperature.
- Packing material : Use material to absorb shocks when grinding wheels are handled.

8. Exposure controls/personal protection

Standard Control Concentration : 3.0mg/m³ Industrial Safety Health Act
 Occupational Exposure Limits (OELs) : Class 2 Respirable dust=1mg/m³
 Total dust 4mg/m³ Japan Society for Occupational Health (2005)

Occupational Exposure Limits (OELs) for composed substances

: Aluminum Oxide : ACGIH TLV-TWA 10mg/m³ (Do not include asbestos nor ≥1% crystalline silica.)
 Amorphous Silica : No data
 Diboron Trioxide : TLV-TWA 10mg/m³

Engineering control : To control dust, install dust collectors or use general ventilation if appropriate.
 Take measures for the sparks not to reach dust collectors, as it could ignite a fire.

Protective equipments : Workers must wear the protective equipments as follows:
 Respiratory protection : Dust protective mask with national test certificate
 Protection with hands : Spark resistant gloves.
 Eye protection : Fully protective dust-proof glasses.
 Hearing protection : Hearing protection should be worn where required.
 Skin and body protection : Wear helmet, safety shoes and standard work clothes.
 Protective clothing : Wear work clothing of spark resistant material.

Hygiene measures : Installation of water washing equipment is preferable for rinsing mouth or eyes.

9. Physical and chemical properties

Appearance (physical state, colour etc) : Grinding wheels are coloured articles, solid, the volume density is 1.4-2.5g/cm³, and insoluble in water

The physical and chemical properties of each substance are as below

	Amorphous Silica	Aluminum Oxide	Diboron Trioxide
Appearance (physical state, colour etc)	Colourless amorphous powder	White crystalline power	Colourless, hygroscopic, brittle, vitreous lumps or hard white crystals, with slightly bitter taste
Odour	No data	Odourless	Odourless
pH	No data	No data	5.1 at 20°C, 1.0% solution
Melting point/freezing point	1610°C (Melting point)	2053 °C	About 450°C (Melting point)
Boiling point, initial boiling	2230°C (Boiling point)	2980°C	About 1,860°C (Boiling point)
Flash point	Not combustible	Not combustible	Not combustible
Upper/lower flammability or	No data	No data	Not combustible
Vapour pressure	1333Pa(1732°C)	0.073Pa (mp.)	Negligible at 20 °C
Vapour density (air=1)	No data	No data	No data
Relative density	2.5	3.97	2.46 (Crystal)
Solubility(ies)	Insoluble in water	Insoluble in water Slightly soluble in non-polar organic solvents	2.77g/100g water at 20 °C
Partition coefficient: n-	No data	No data	No data
Auto-ignition temperature	Not combustible	Not combustible	Not combustible
Decomposition temperature	No data	No data	No data
Odour threshold	No data	No data	No data
Evaporation rate (Butyl Acetate =	No data	Not applicable	Not applicable
Flammability (solid, gas)	No data	Not combustible	Not combustible
Viscosity	No data	No data	Not applicable

10. Stability and reactivity

Stability : Stable under normal conditions
 Reactivity : None known
 Conditions to avoid (e.g. static discharge, shock or vibration) : High temperatures, high humidity or shocks
 Incompatible materials : None known
 Hazardous decomposition products : None known

1 1 . Toxicological information

Aspiration toxicity of grinding wheels

If inhaled dust during grinding operation through prolonged exposure, it may cause pneumoconiosis.

Specific considerations concerning toxicological information of composed substances are as below

	Aluminum Oxide	Amorphous Silica	Diboron Trioxide	
Acute toxicity	Oral	Rat: LD50 > 5000mg/kg	Rat LD ₅₀ =5mg/kg	Category 5 May be harmful if swallowed
	Dermal	No data	Physical irritation may occur although specific data cannot be found.	No data
	Inhalation (Dusts, mists)	No data	Rat: LCL ₀ =2190mg/m ³ /4H	Classification not possible
Skin corrosion/irritation	No data	Physical irritation may occur although specific data cannot be found.	Category 3 Rabbit: Erythema ((ACGIH (2001)) Humans: The substance irritates the skin (ICSC (1994))	
Serious eye damage/eye irritation	No data	The substance has potential to cause irritation.Rabbit: 25mg/24H	Category 2A or 2B Causes serious eye irritation Animal: Conjunctivitis Human: Redness, pain; The substance irritates the eyes.	
Respiratory or skin sensitization	No data	No data	No data	
Germ cell mutagenicity	Lack of data	No data	No data	
Carcinogenicity	ACGIH: A4 (Not classifiable as a human carcinogen)	IARC Classification: 3 (Not classifiable as to carcinogenicity in humans)	No data	
Reproductive toxicity	No data	No information	No information	
Specific target organ and systemic toxicity following single exposure	Category 3 (Respiratory tract irritation) Upper respiratory tract irritation (ICSC (2000))	No information	Category 3 May cause respiratory irritation Humans: Irritation of nose or throat; respiratory symptoms such as cough, stuffiness, dyspnea, and sore throat.	
Specific target organ and systemic toxicity -Repeated exposure	Category 1 Pulmonary fibrosis (Occupational exposure) (EHC (1997)) Causes damage to organs through prolonged or repeated exposure (Inhalation: Lungs)	No information	Lack of data	
Aspiration hazard	No data	No data	No data	

1 2 . Ecological information

Persistence and degradability : No findings

Bioaccumulative potential : No findings

Mobility in soil : No findings

Other adverse effects : Grinding chips (including dust and mist) are generated during cutting and grinding.

Specific considerations concerning toxicological information of composed substances are as below.

	Aluminum Oxide	Amorphous Silica	Diboron Trioxide
Acute hazards to the aquatic environment	Lack of data	Lack of data	Crustacea (Daphnia magna): 48 hours EC ₅₀ = 370 - 490 mg/L (IUCLID (2000)) Concentration equivalent: 2382-3155 mg/L
Long-term hazards to the aquatic environment	Lack of data	Lack of data	Water solubility 27700mg/L (HSDB (2004)) Low acute aquatic toxicity

1 3 . Disposal considerations

Waste from residues : For proper disposal, follow the related regulations and standards of local authority.

Contract with authorized industrial waste disposal contractor with contents clarification.

Sort the waste into glass, concrete and ceramic wastes and dispose as industrial waste.

May elute into soil or water.

Contaminated container and packaging : No findings

1 4 . Transport information

International regulation

Regulatory information on sea transportation : Not regulated as dangerous goods

Regulatory information on air transportation : Not regulated as dangerous goods

Domestic regulation

Regulatory information on ground transportation: No regulatory information

Regulatory information on sea transportation : Not regulated as dangerous goods

Regulatory information on air transportation : Not regulated as dangerous goods

Special precautions : Keep dry and be aware not to damage the packaging.

- Use container with inner packaging, to absorb some degree of pressure, shocks, and of damp-proof property.
- Handle grinding wheels carefully to prevent damaging.
- Transport grinding wheels without rolling, dropping and bumping. As they are breakables, do not through or drop.
- Report the manufacturer or users in case they have possibly given unusual shocks or pressures.

1 5 . Regulatory information

Industrial Safety and Health Act, Japan

- Dangerous and Toxic Substances Subject to Notify Their Names
(Article 57-2, Enforcement Order 18-2, Appended Table 9)
- Special Education pertaining work involving replacement of grinding wheels
(Article 59-3, Rules on Special Education for Safety and Health, Article 1)
- Precaution for handling (Ordinance on Industrial Safety and Health, Part II)
- Provided with safety devices (Article 13 of the Order for Enforcement of the Industrial Safety and Health Act)

Ordinance on Prevention of Dangers Due to Dust, Japan : Dust work(Chapter 1 Article 2)

Safety requirement for use, care and protection of abrasive wheel and grinder, Japan : Operating and manufacturing precautions

Law concerning Pollutant Release and Transfer Register, Japan : Not applicable

Soil Contamination Countermeasure Act, Japan

Water Pollution Control Act, Japan

1 6 . Regulatory information

Other information

[Safety Manual for Grinders]

Japan Industrial Safety & Health Association , Japan Society for Occupational Health , ACGIH (American Conference of Governmental Industrial Hygienists)

http://www.jaish.gr.jp/user/anzen/kag/kag_main01.html

Kure Grinding Wheel, Co., Ltd makes no warranty with the content or Physical and Chemical Properties of any specific substance as described in this Material Safety Data Sheet.

Users must be responsible for handling the data with precautions, as the evaluation of hazardous properties of substances is based on the materials, information and data available as of the date this Material Safety Data Sheet was created by Kure Grinding Wheel, Co., Ltd, however, the materials, information and data are not exhaustive.